




Anschlagpunkte

Gewindesonderlängen auf Anfrage



Anschlagpunkt GK 10

- 90° Arbeitsbereich
- 360° drehbar
- mit Spannbügel
- Sehr flache Bauform



Artikel Article	Nenngröße Diameter	Maße in mm Dimensions in mm									Gewicht Weight	Drehmoment Torque	Reparatur Set Repair Kits
		mm	A	B	D	E	F	G	H	S			
8-211-003G	M8 x 1,25	30	35	10,0	11	85	55	35	6	13	0,20	30	8-P211-003
8-211-006G	M10 x 1,50	30	35	10,0	16	85	55	36	8	17	0,30	60	8-P211-006
8-211-010G	M12 x 1,75	33	37	13,5	18	98	57	44	8	19	0,50	100	8-P211-010
8-211-012G	M14 x 2,00	33	37	13,5	21	98	57	45	10	22	0,50	120	8-P211-012
8-211-015G	M16 x 2,00	33	37	13,5	24	98	57	46	10	24	0,50	150	8-P211-015
8-211-020G	M18 x 2,00	50	54	16,5	26	140	82	57	12	30	1,30	200	8-P211-020
8-211-025G	M20 x 2,50	50	54	16,5	30	140	82	57	12	30	1,30	250	8-P211-025
8-211-040G	M24 x 3,00	50	54	16,5	36	140	82	59	14	36	1,40	400	8-P211-040
8-211-042G	M27 x 3,00	60	65	22,5	38	170	99	79	17	41	2,80	400	8-P211-042
8-211-050G	M30 x 3,50	60	65	22,5	48	170	99	81	17	46	3,10	500	8-P211-050
8-211-070G	M36 x 4,00	60	65	22,5	54	178	99	88	22	55	3,30	700	8-P211-070
8-211-080G	M36 x 4,00	77	85	26,5	62	225	124	101	22	55	5,80	800	8-P211-080
8-211-100G	M42 x 4,50	77	85	26,5	72	225	124	104	24	65	6,30	1.000	8-P211-100
8-211-150G	M42 x 4,50	95	104	36,0	57	256	158	112	24	65	10,80	1.500	8-P211-150
8-211-200G	M48 x 5,00	95	104	36,0	72	259	158	120	27	75	11,60	2.000	8-P211-200

Artikel Article	Gewinde Thread	Tragfähigkeit in to WLL in to									
		1 0°	2 0°	1 90°	2 90°	2 0-45°	2 45-60°	2 unsymm.	3-4 0-45°	3-4 45-60°	3-4 unsymm.
8-211-003G	M 8	0,30	0,60	0,30	0,60	0,42	0,30	0,30	0,63	0,45	0,30
8-211-006G	M10	0,63	1,26	0,63	1,26	0,88	0,63	0,63	1,32	0,95	0,63
8-211-010G	M12	1,00	2,00	1,00	2,00	1,40	1,00	1,00	2,10	1,50	1,00
8-211-012G	M14	1,20	2,40	1,20	2,40	1,70	1,20	1,20	2,50	1,80	1,20
8-211-015G	M16	1,50	3,00	1,50	3,00	2,10	1,50	1,50	3,10	2,20	1,50
8-211-020G	M18	2,00	4,00	2,00	4,00	2,80	2,00	2,00	4,20	3,00	2,00
8-211-025G	M20	2,50	5,00	2,50	5,00	3,50	2,50	2,50	5,20	3,70	2,50
8-211-040G	M24	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00
8-211-042G	M27	4,00	8,00	4,00	8,00	5,60	4,00	4,00	8,40	6,00	4,00
8-211-050G	M30	5,00	10,00	5,00	10,00	7,00	5,00	5,00	10,50	7,50	5,00
8-211-070G	M36	7,00	14,00	7,00	14,00	9,80	7,00	7,00	17,70	10,50	7,00
8-211-080G	M36	8,00	16,00	8,00	16,00	11,20	8,00	8,00	16,80	12,00	8,00
8-211-100G	M42	10,00	20,00	10,00	20,00	14,00	10,00	10,00	21,00	15,00	10,00
8-211-150G	M42	15,00	30,00	15,00	30,00	21,00	15,00	15,00	31,50	22,50	15,00
8-211-200G	M48	20,00	40,00	20,00	40,00	28,00	20,00	20,00	42,00	30,00	20,00